

16x32 Pool & Deck Materials List

MATERIALS LIST

(All Pool Lumber, CCA .6 Pressure-Treated for in-ground use. Treatment is available on special-order through most lumber yards. Allow 2-3 weeks for treating process. All treated lumber, construction fir and ACX Exterior Plywood

LUMBER:

Plywood: 12- 4'x8'x 3/4" Panels/ 4x4"s: 12- 6'; 1- 8'/ 2x6"s: 53- 8'/ 2x4"s: 8- 8'/

HARDWARE:

10 lbs. 3-1/2" Galv. Box Nails/ 2 lbs. 1-1/2" Galv. Box Nails/

CONCRETE SUPPLIES:

"Ready-Crete: 18- 60-lb Bags/ Portland Cement: 12- 1 cu.ft. Bags/
Concrete Pool Base Aggregate (or "Provovil"): 24- 4 cu.ft. Bags/

POOL COMPONENTS: (See Supply Catalogue for details)

16'x 32' Tailored Vinyl Liner (Dimensions shown in Fig. #4)
1- HP PUMP
1- FILTER (for 15000 Gal. Pool)
1- SURFACE SKIMMER Filter Inlet for Vinyl Pool
1- 1-1/2" THROUGH-WALL FITTING for Vinyl Pool
96' Molded LINER TRACK
96' Roll 39"x 1/4" INSULATION FOAM

REEL BACK COVER & FRAMES:

(Pressure-Treated Plywood and Lumber for in-ground use)
1- 4'x8'x 3/4" Plywood Panel/ 1- 16"x 32"x 3/4" Plywood Scrap (no Treatment needed) Rough 4x4"s: 2- 8'/ 2x2"s: 2-6'/2x4"s: 4- 8'/ 8- 4" Lag Screws/ Pipe Fittings, all Galv. 1/2": 2- four-hole Floor Flanges
4- 90° Elbows/4- 4" Pipes/ 2- 6" Pipes/ 2- 1-1/4" Pipes/4- 1" Washers/
2- Cotter Pins/4- 8' Lengths, 1/2" Alum. C-Channel Molding/ 32- 5/8" #8 Sheetmetal Screws/1- 36'x 26' Solar Pool Cover.

DECKING (as shown)

Framing: (Rough 2x4" Stock): Pool Cover Beam; 8- 8'/ Pool Perimeter; 4- 12', 4- 8'/ Deck Perimeter; 8- 12', 4-10'/ Joists; 24- 8', 9- 10' Tail-Joists; 160 Lineal Feet/
DECKING: (Finished 2x4 Cedar 2x4" Stock): 1632 Lineal Feet.
FACIA: 6- 16' 2x6" Stock (with nice grain)/ 12- 8'x 1" Plastic Molding/
20-lbs, 3-1/2" Galv. Finishing Nails/ 1-box 1" Panelling Nails